

© Copyright SEK. Reproduction in any form without permission is prohibited.

Järnvägsanläggningar – Kompatibilitet mellan rälsfordon och fordonsdetekterande system – Del 2: Kompatibilitet med spårledningar

Railway applications –

Compatibility between rolling stock and train detection systems –

Part 2: Compatibility with track circuits

(CENELEC Technical Specification 50238-2:2015, CLC/TS 50238-2:2015/AC:2016-07)

Nationellt förord

En teknisk specifikation, TS, utarbetad inom CENELEC är avsedd att ge beskrivningar som kan stödja den inre marknadens utveckling, ge vägledning beträffande specifikationer eller provningsmetoder eller ge specifikationer för teknikområden under snabb utveckling. Ett förslag till europeisk standard, EN, som det inte varit möjligt att nå tillräcklig enighet kring, kan också fastställas som TS, för att användas på försök (som förstandard) och för att efter eventuella justeringar eller bearbetningar senare fastställas som EN. En teknisk specifikation har en giltighetstid som är begränsad till tre år, med möjlighet till förlängning med tre eller högst sex år.

Tidigare fastställd svensk standard SEK TS 50238-2, utgåva 1, 2011, gäller ej fr o m 2017-11-23.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English Version

Railway applications - Compatibility between rolling stock and train detection systems - Part 2: Compatibility with track circuits

Applications ferroviaires - Compatibilité entre le matériel roulant et les systèmes de détection des trains - Partie 2 - Compatibilité avec les circuits de voie

Bahnanwendungen - Kompatibilität zwischen Fahrzeugen und Gleisfreimeldesystemen - Teil 2: Kompatibilität mit Gleisstromkreisen

This Technical Specification was approved by CENELEC on 2015-04-20.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels



Corrigendum to CLC/TS 50238-2:2015

English version

In Table A.1, correct the frequency value for track circuit UGSK3 "222,45" with the correct value of "225,45" Hz to read:

"

UGSK 3	225,45	4	6,5	14	6	0,5		
--------	--------	---	-----	----	---	-----	--	--

"

July 2016

Contents

Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms, definitions and abbreviations.....	8
3.1 Terms and definitions	8
3.2 Abbreviations	9
4 General aspects of interference current limits for RST.....	10
4.1 Derivation of interference current limits for RST.....	10
4.2 Application of Interference current limits to RST design	11
4.3 System definition	11
Annex A (normative) Interference current limits for RST	14
A.1 Definitions	14
A.2 Preferred track circuits for DC traction.....	14
A.3 Preferred track circuits for RST for 16,7 Hz traction	15
A.4 Preferred track circuits for RST for 50 Hz traction	15
A.5 UGSK3	16
A.6 UGSK95	16
A.7 FTGS 46 / FTGS 917/TCM100	16
A.8 GRS	17
A.9 Jade	17
A.10 Coded track circuits for DC traction.....	18
A.11 Digicode	18
A.12 CoRTo	18
A.13 CBDAC.....	19
A.14 Preferred track circuit in Czech Republic	19
A.15 All kind of UM71 equipped with RENUM receptor and UC 9500.....	20
A.16 DC track circuits in UK	20
A.17 EBI Track 200 (TI21)	21
A.18 EBI Track 400	21
A.19 FS3000	22
A.20 FS2000 / FS 2500 / FS 2550 / FS 5000	23
A.21 Track circuits of 95 Hz and 105 Hz in Norway	23
A.22 JRK 10470	24
Annex B (normative) Rolling Stock Interference Evaluation methods.....	25
B.1 General	25
B.2 Selected evaluation method.....	25
B.3 Derivation of the interference current limits for RST	26
B.4 Criteria for compatibility	27
B.4.1 Location	27
B.4.2 Criteria 27	

B.4.3	Safety and availability.....	27
B.5	Defined interference current limits for RST: for use under interoperability regulation.....	27
B.6	Test specifications for RST interference measurements.....	27
B.6.1	General	27
B.6.2	Purpose of compatibility tests.....	28
B.7	Test equipment requirements (hardware)	31
B.8	Train interference analysis and evaluation methods	31
B.8.1	Evaluation method	31
B.8.2	Summation rules	32
B.9	Requirements for on-train interference monitoring and control	33
B.10	Documentation	34
Annex C (informative)	Infrastructure data	35
C.1	Supply frequency	35
C.2	Infrastructure characterization	35
C.3	Power supply impedance	36
C.4	Approximate calculation of the lowest power supply resonance frequency.....	36
C.5	Simplified method to handle resonance effects with roof cables	37
C.6	Return current transfer function.....	39
Annex D (informative)	Typical voltage resonance graphs.....	40
D.1	General	40
D.2	Interface voltage/current measurement.....	40
D.3	Voltage resonance graphs for 15 kV 16,7 Hz network.....	40
D.4	Voltage resonance graphs for 25 kV, 50 Hz network.....	41
D.5	Voltage resonance graphs for 1 500 V DC network	41
D.6	Voltage resonance graphs for 3 000 V DC network.....	42
Bibliography		43

Figures

Figure 1 — Examples of IUs	9
Figure 2 — System configuration considered for interference.....	12
Figure B.1 — Time domain method	26
Figure B.2 — Superposition factors.....	33
Figure C.1 — Infrastructure characterization	35
Figure C.2 — Power supply admittance	36
Figure C.3 — Resonance effects for various RST positions.....	38
Figure C.4 — Resonance effects for various RST input capacitance.....	39
Figure D.1 — Voltage resonance graph for 15 kV 16,7 Hz network.....	41
Figure D.2 — Voltage resonance graphs for 25 kV 50 Hz network.....	41
Figure D.3 — Voltage resonance graphs for 1 500 V DC network.....	42
Figure D.4 — Impedance graphs for 3 000 V DC network.....	42

Tables

Table A.1 — UGSK3	16
Table A.2 — UGSK95	16
Table A.3 — FTGS/TCM100	16
Table A.4 — GRS	17
Table A.5 — GRS - limits due to rectifying traction supply	17
Table A.6 — Jade 25 kV, 50 Hz lines	17
Table A.7 — Jade DC lines	18
Table A.8 — Limits for BACC and CDB 83,3 Hz	18
Table A.9 — Digicode.....	18
Table A.10 — CoRTo.....	18
Table A.11 — CBDAC.....	19
Table A.12 — 50 Hz AC and DC Traction.....	19
Table A.13 — UM71 C, UM71 CB, UM71C TVM and UC9500	20
Table A.14 — DC track circuits in UK.....	20
Table A.15 — EBI Track 200 (TI-21) Double Rail Limit for in-band frequencies — AC traction only	21
Table A.16 — EBI Track 200 (TI-21) Double Rail Limit for in-band frequencies — DC traction or non-electrified lines	21
Table A.17 — EBI Track 400 Open Line Frequency Double Rail Track Circuit Limit for in-band frequencies	21
Table A.18 — EBI Track 400 Open Line Frequency Double Rail Track Circuit Limit for out of band frequencies.....	22
Table A.19 — EBI Track 400 Station Area Frequency Double Rail Track Circuit Limit.....	22
Table A.20 — FS3000 3 kV, DC lines	22
Table A.21 — FS3000 25 kV, 50 Hz lines.....	23
Table A.22 — FS2000 / FS 2500 / FS 2550 / FS 5000 3 kV, DC lines.....	23
Table A.23 — Track circuits of 95 Hz and 105 Hz in Norway	23
Table A.24 — JRK 10470	24
Table B.1 — Reduction factors for capacitive input impedance	30
Table B.2 — Summation categories.....	32
Table B.3 — K factor values	33
Table C.1 — Supply frequency	35
Table C.2 — Capacitance parameters for electrified lines.....	37
Table C.3 — No-load supply voltage levels	37
Table D.1 — Measurement parameters	40
Table D.2 — Measurement frequencies.....	40

Foreword

This document (CLC/TS 50238-2:2015) has been prepared by CLC/SC 9XA "Communication, signalling and processing systems" of Technical Committee CLC/TC 9X, "Electrical and electronic applications for railways".

This document supersedes CLC/TS 50238-2:2010.

CLC/TS 50238-2:2015 includes the following significant technical changes with respect to CLC/TS 50238-2:2010:

- The interference current limits for RST have been updated in the normative Annex A.
- The measurement and evaluation methods for verifying conformity of rolling stock to the limits for interference current emissions have been moved to the new normative Annex B.

This Technical Specification is intended to become Part 2 of the EN 50238 series published under the title *Railway applications — Compatibility between rolling stock and train detection systems*. The series consists of:

- *Part 1: General*¹⁾;
- *Part 2: Compatibility with track circuits* [this document];
- *Part 3: Compatibility with axle counters*.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

1) The existing EN 50238:2003 was renumbered EN 50238-1 when the voting procedure on Parts 2 and 3 was closed.

Introduction

This Technical Specification is being developed to permit compliance with the Interoperability Directives (High Speed and Conventional).

This Part 2 of the series defines:

- a set of interference current limits for rolling stock based on defined track circuits,
- measurement and evaluation methods to verify rolling stock interference current emissions and demonstrate compatibility with the track circuits;
- traceability of compatibility requirements (types of track circuit and associated limits).

1 Scope

This Technical Specification defines, for the purpose of ensuring compatibility between rolling stock and track circuits, the limits for interference current emissions from rolling stock. The measurement and evaluation methods for verifying conformity of rolling stock to these limits are presented in a dedicated annex.

The interference limits are only applicable to interoperable rolling stock which is intended to run on lines exclusively equipped with preferred track circuits listed in this Technical Specification. National Notified Technical Rules are still to be used in all cases, where the line over which the rolling stock is intended to run is equipped with any type of older version or non-preferred track circuits that are not listed in this Technical Specification. However, the rolling stock test methodology (infrastructure conditions, test configurations, operational conditions, etc.) presented in this Technical Specification is also applicable to establish compatibility with non-preferred track circuits.

This Technical Specification gives guidance on the derivation of interference current limits specified for rolling stock and defines measurement methods and evaluation criteria in a dedicated annex.

This Technical Specification defines:

- a) a set of interference current limits for RST (Rolling Stock) applicable for each of the following types of traction system:
 - 1) DC (750 V, 1,5 kV and 3 kV);
 - 2) 16,7 Hz AC;
 - 3) 50 Hz AC;
- b) methodology for the demonstration of compatibility between rolling stock and track circuits;
- c) measurement method to verify interference current limits and evaluation criteria.

NOTE 1 The basic parameters of track circuits associated with the interference current limits for RST are not in the scope of this Technical Specification.

NOTE 2 Any phenomena linked to traction power supply and associated protection (over voltage, short-circuit current, under- and over-voltage if regenerative brakes are used) is part of the track circuit design and outside the scope of this Technical Specification.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50126 (all parts), *Railway applications — The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS)*

EN 50128, *Railway applications — Communication, signalling and processing systems — Software for railway control and protection systems*

EN 50129, *Railway applications — Communication, signalling and processing systems — Safety related electronic systems for signalling*

EN 50238-1:2003, *Railway applications — Compatibility between rolling stock and train detection systems — Part 1: General*

CLC/TS 50238-3:2013, *Railway applications — Compatibility between rolling stock and train detection systems — Part 3: Compatibility with axle counters*

EN 50388, *Railway Applications — Power supply and rolling stock — Technical criteria for the coordination between power supply (substation) and rolling stock to achieve interoperability*

CLC/TR 50507, *Railway applications — Interference limits of existing track circuits used on European railways*

UIC 550, *Power supply installations for passenger stock*