

© Copyright SEK. Reproduction in any form without permission is prohibited.

**Järnvägsanläggningar –  
Kompatibilitet mellan rälsfordon och fordonsdetekterande system –  
Del 2: Kompatibilitet med spårledningar**

*Railway applications –  
Compatibility between rolling stock and train detection systems –  
Part 2: Compatibility with track circuits  
(CENELEC TS 50238-2:2010<sup>\*)</sup>)*

En teknisk specifikation, TS, utarbetad inom CENELEC är avsedd att ge beskrivningar som kan stödja den inre marknadens utveckling, ge vägledning beträffande specifikationer eller provningsmetoder eller ge specifikationer för teknikområden under snabb utveckling. Ett förslag till europeisk standard, EN, som det inte varit möjligt att nå tillräcklig enighet kring, kan också fastställas som TS, för att användas på försök (som förstandard) och i syfte att efter eventuella justeringar eller bearbetningar senare fastställas som EN. En teknisk specifikation har en giltighetstid som inledningsvis är begränsad till tre år, men som kan förlängas ytterligare tre år.

---

<sup>\*)</sup> Corrigendum February 2011 ingår i standarden.

## *Standarder underlättar utvecklingen och höjer elsäkerheten*

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

## *SEK är Sveriges röst i standardiseringssarbetet inom elområdet*

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

## *Stora delar av arbetet sker internationellt*

Utdriften av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringssarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringssverksamhet och medlemsavgift till IEC och CENELEC.

## *Var med och påverka!*

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtidens standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

## **SEK Svensk Elstandard**

Box 1284  
164 29 Kista  
Tel 08-444 14 00  
[www.elstandard.se](http://www.elstandard.se)

**TECHNICAL SPECIFICATION**  
**SPÉCIFICATION TECHNIQUE**  
**TECHNISCHE SPEZIFIKATION**

**CLC/TS 50238-2**

July 2010

ICS 29.280; 45.060.10

English version

**Railway applications -  
Compatibility between rolling stock and train detection systems -  
Part 2: Compatibility with track circuits**

Applications ferroviaires -  
Compatibilité entre le matériel roulant  
et les systèmes de détection des trains -  
Partie 2: Compatibilité avec les circuits  
de voie

Bahnanwendungen -  
Kompatibilität zwischen Fahrzeugen  
und Gleisfreimeldesystemen -  
Teil 2: Kompatibilität  
mit Gleisstromkreisen

This Technical Specification was approved by CENELEC on 2010-07-07.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Management Centre: Avenue Marnix 17, B - 1000 Brussels**

© 2010 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Ref. No. CLC/TS 50238-2:2010 E

## Foreword

This Technical Specification was prepared by SC 9XA, Communication, signalling and processing systems, of Technical Committee CENELEC TC 9X, Electrical and electronic applications for railways.

It was circulated for voting in accordance with the Internal Regulations, Part 2, Subclause 11.3.3.3 and was approved by CENELEC as CLC/TS 50238-3 on 2010-07-09.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following date was fixed:

- latest date by which the existence of the CLC/TS has to be announced at national level (doa) 2011-01-07

This Technical Specification is intended to become Part 2 of the series EN/TS 50238 published under the title '*Railway applications - Compatibility between rolling stock and train detection systems*'. The series consists of:

- Part 1: General <sup>1)</sup>
  - Part 2: Compatibility with track circuits (this document)
  - Part 3: Compatibility with axle counters.
- 

<sup>1)</sup> Existing EN 50238:2003 was renumbered EN 50238-1 once the voting procedure on Parts 2 & 3 was closed.

## Contents

<b>Introduction .....</b>	<b>6</b>
<b>1 Scope .....</b>	<b>7</b>
<b>2 Normative references .....</b>	<b>7</b>
<b>3 Terms, definitions and abbreviations .....</b>	<b>8</b>
3.1 Terms and definitions .....	8
3.2 Abbreviations .....	9
<b>4 General aspects of interference current limits for RST .....</b>	<b>10</b>
4.1 Derivation of interference current limits for RST .....	10
4.2 Application of Interference current limits to RST design .....	10
4.3 System definition .....	11
<b>5 Evaluation methods .....</b>	<b>12</b>
5.1 General .....	12
5.2 Selected evaluation method .....	13
5.3 Derivation of the interference current limits for RST and margins .....	13
5.4 Criteria for compatibility .....	14
<b>6 Defined interference current limits for RST for use under interoperability regulations .....</b>	<b>15</b>
6.1 Preferred track circuits for DC traction .....	15
6.2 Preferred track circuits for RST for 16,7 Hz traction .....	16
6.3 Preferred track circuits for RST for 50 Hz traction .....	16
<b>7 Test specifications for RST interference measurements .....</b>	<b>16</b>
7.1 Purpose of compatibility tests .....	17
7.2 Test equipment requirements (hardware) .....	19
<b>8 Train interference analysis and evaluation methods .....</b>	<b>20</b>
8.1 Evaluation method .....	20
8.2 Requirements for on-train interference monitoring and control .....	23
8.3 Documentation .....	23
<b>Definitions .....</b>	<b>24</b>
<b>A.1 UGSK3 .....</b>	<b>24</b>
<b>A.2 UGSK95 .....</b>	<b>25</b>
<b>A.3 FTGS 46 / FTGS 917 .....</b>	<b>25</b>
<b>A.4 GRS .....</b>	<b>25</b>
<b>A.5 Jade .....</b>	<b>26</b>
<b>A.6 Coded track circuits for DC traction .....</b>	<b>27</b>
<b>A.7 Digicode .....</b>	<b>27</b>
<b>A.8 CBDAC .....</b>	<b>28</b>
<b>A.9 Preferred track circuit in Czech Republic .....</b>	<b>28</b>
<b>A.10 UM71 C, UM71 CB, UM71 C TVM and SJB .....</b>	<b>29</b>
<b>A.11 DC track circuits in UK .....</b>	<b>29</b>
<b>A.12 EBI Track 200 (TI21) .....</b>	<b>30</b>
<b>A.13 FS3000 .....</b>	<b>30</b>
<b>A.14 FS2000 / FS 2500 / FS 2550 / FS 5000 .....</b>	<b>31</b>
<b>A.15 Track circuits of 95 Hz and 105 Hz in Norway .....</b>	<b>31</b>
<b>A.16 JRK 10470 .....</b>	<b>32</b>

<b>B.1 Supply frequency .....</b>	<b>33</b>
<b>B.2 Infrastructure characterisation.....</b>	<b>33</b>
<b>B.3 Power supply impedance .....</b>	<b>34</b>
<b>B.4 Approximate calculation of the lowest power supply resonance frequency .....</b>	<b>34</b>
<b>B.5 Simplified method to handle resonance effects with roof cables .....</b>	<b>35</b>
<b>B.6 Return current transfer function.....</b>	<b>37</b>
<b>C.1 Interface voltage/current measurement .....</b>	<b>38</b>
<b>C.2 Voltage resonance graphs for 15 kV 16,7 Hz network .....</b>	<b>38</b>
<b>C.3 Voltage resonance graphs for 25 kV, 50 Hz network .....</b>	<b>39</b>
<b>C.4 Voltage resonance graphs for 1 500 V DC network .....</b>	<b>39</b>
<b>C.5 Voltage resonance graphs for 3 000 V DC network .....</b>	<b>40</b>

**Figures**

<b>Figure 1 – Examples of IUs .....</b>	<b>9</b>
<b>Figure 2 - System configuration considered for interference .....</b>	<b>11</b>
<b>Figure 3 – Time domain method .....</b>	<b>13</b>
<b>Figure 4 - Margins for track circuit interference current limits.....</b>	<b>14</b>
<b>Figure 5 - Superposition factors.....</b>	<b>22</b>
<b>Figure B.1 - Infrastructure characterisation.....</b>	<b>33</b>
<b>Figure B.2 - Power supply admittance.....</b>	<b>34</b>
<b>Figure B.3 – Resonance effects for various RST positions.....</b>	<b>36</b>
<b>Figure B.4 – Resonance effects for various RST input capacitance .....</b>	<b>37</b>
<b>Figure C.1 - Voltage resonance graph for 15 kV 16,7 Hz network .....</b>	<b>39</b>
<b>Figure C.2 - Voltage resonance graphs for 25 kV 50 Hz network .....</b>	<b>39</b>
<b>Figure C.3 - Voltage resonance graphs for 1 500 V DC network .....</b>	<b>40</b>
<b>Figure C.4 - Impedance graphs for 3 000 V DC network .....</b>	<b>40</b>

**Tables**

<b>Table 1 - Reduction factors for capacitive input impedance .....</b>	<b>19</b>
<b>Table 2 - Summation categories .....</b>	<b>21</b>
<b>Table 3 - K factor values .....</b>	<b>22</b>
<b>Table A.1 - UGSK3 .....</b>	<b>24</b>
<b>Table A.2 – UGSK95 .....</b>	<b>25</b>
<b>Table A.3 - FTGS.....</b>	<b>25</b>
<b>Table A.4 - GRS .....</b>	<b>25</b>
<b>Table A.5 - GRS - limits due to rectifying traction supply .....</b>	<b>26</b>
<b>Table A.6 - Jade 25 kV, 50 Hz lines .....</b>	<b>26</b>
<b>Table A.7 - Jade DC lines .....</b>	<b>26</b>
<b>Table A.8 - Limits for BACC and CDB 83,3 Hz.....</b>	<b>27</b>
<b>Table A.9 - Digicode .....</b>	<b>27</b>
<b>Table A.10 - CBDAC.....</b>	<b>28</b>
<b>Table A.11 - DC Traction .....</b>	<b>28</b>
<b>Table A.12 – 50 Hz AC Traction.....</b>	<b>28</b>

<b>Table A.13 - UM 71 CB and UM71 C TVM SEI .....</b>	<b>29</b>
<b>Table A.14 - DC track circuits in UK .....</b>	<b>29</b>
<b>Table A.15 - EBI Track 200 (TI21).....</b>	<b>30</b>
<b>Table A.16 - FS3000 3 kV, DC lines.....</b>	<b>30</b>
<b>Table A.17 - FS3000 25 kV, 50 Hz lines.....</b>	<b>31</b>
<b>Table A.18 - FS2000 / FS 2500 / FS 2550 / FS 5000 3 kV, DC lines.....</b>	<b>31</b>
<b>Table A.19 - Track circuits of 95 Hz and 105 Hz in Norway .....</b>	<b>31</b>
<b>Table A.20 – JRK 10470.....</b>	<b>32</b>
<b>Table B.1 - Supply frequency.....</b>	<b>33</b>
<b>Table B.2 - Capacitance parameters for electrified lines.....</b>	<b>35</b>
<b>Table B.3 - No-load supply voltage levels .....</b>	<b>35</b>
<b>Table C.1 - Measurement parameters .....</b>	<b>38</b>
<b>Table C.2 - Measurement frequencies .....</b>	<b>38</b>

## Introduction

This Technical Specification is being developed to permit compliance with the Interoperability Directives (High Speed and Conventional).

This Part 2 of the series defines

- a set of interference current limits for rolling stock based on defined track circuits,
- measurement methods to verify rolling stock interference current emissions and demonstrate compatibility with the track circuits,
- traceability of compatibility requirements (types of track circuit and associated limits).

## 1 Scope

This Technical Specification defines, for the purpose of ensuring compatibility between rolling stock and track circuits the limits for conducted interference from rolling stock and the measurement method for verifying conformity of rolling stock to these limits.

The interference limits are only applicable to interoperable rolling stock which is intended to run on lines exclusively equipped with preferred track circuit listed in this Technical Specification. National Notified Technical Rules are still to be used in all cases, where the line over which the rolling stock is intended to run is equipped with any type of older version or non-preferred track circuits that are not listed in this Technical Specification. However, the rolling stock test methodology (infrastructure conditions, test configurations, operational conditions, etc.) presented in this Technical Specification is also applicable to establish compatibility with non-preferred track circuits.

This Technical Specification gives guidance on the derivation of interference current limits specified for rolling stock and defines measurement methods and evaluation criteria.

This Technical Specification defines

- a set of interference current limits for RST (Rolling Stock) applicable for each of the following types of traction system:
  - DC (750 V, 1,5 kV and 3 kV);
  - 16,7 Hz AC;
  - 50 Hz AC.
- methodology for the demonstration of compatibility between rolling stock and track circuits,
- measurement method to verify interference current limits and evaluation criteria.

NOTE 1 The basic parameters of track circuits associated with the interference current limits for RST are not in the scope of this Technical Specification.

NOTE 2 Any phenomena linked to traction power supply and associated protection (over voltage, short-circuit current, under- and over-voltage if regenerative brakes are used) is part of the track circuit design and outside the scope of this Technical Specification.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN/TR 50126 series, Railway applications - The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS)

EN 50128, Railway applications - Communication, signalling and processing systems - Software for railway control and protection systems

EN 50129, Railway applications - Communication, signalling and processing systems - Safety related electronic systems for signalling

EN 50163, Railway applications - Supply voltages of traction systems

EN 50238, Railway applications - Compatibility between rolling stock and train detection systems

EN 50388, Railway applications - Power supply and rolling stock - Technical criteria for the coordination between power supply (substation) and rolling stock to achieve interoperability

CLC/TR 50507, Railway applications - Interference limits of existing track circuits used on European railways

UIC 550, Power Supply Installations for Passenger Stock

ENV 13005, Guide to the expression of uncertainty in measurements